

SERVICE BODY SPECIFICATION J, L, S, T and U-Series

Body Shell

- Body sides, bulkhead, and tailgate are constructed of 14 gauge A40 galvanized steel.
- One piece compartment top and back.
- Die formed seamless fenders.

Floor

- 12 gauge medium pattern treadplate floor.

Understructure

- 5-1/4" high 3/16" formed steel crossmembers at the front of the body.
- 2" x 3" high 10 gauge formed steel extension U-shaped crossmembers.
- 4-3/4" high 3/16" formed steel crossmembers at the rear of the body.
- 3 full-length formed 14 gauge steel "hat" channel longitudinals.

Doors

- Double panel doors with 14 gauge galvanized steel outer panel and 18 gauge corrugated inner panel.
- Door design includes a knife edge for continuous positive contact with the door seal.

Rear Body Reinforcing Member

- 12 gauge "hat" channel reinforcement across the rear of the body.

Hinge Pins and Hinges

- Doors incorporate 5/16" diameter stainless steel rod hinge pins.
- Stainless steel pillow block hinges include self-lubricating plastic bushings.
- Hinge pillow blocks are attached to the body side with closed end pop rivets as standard. Body can be ordered with hinges welded as an option.

Door Retainers

- Spring loaded door retainers on vertical doors are easily detachable to allow the door to swing 180°.
- Heavy-duty chain supports on the horizontal doors are easily removable to allow the door to drop down.

Door Seals

- Automotive type "D" bulb seal installs in a full perimeter protective channel. Seal is unbroken at the striker.

Shelving

- Shelving and compartment partitions are removable allowing for the creation of various compartment interior arrangements.
- 4 full-height compartment partitions are furnished as standard. Half-height partitions are available as an option.
- Compartment shelving is adjustable on 2" centers.
- 16 gauge galvanized steel shelves are slotted for dividers on 2" centers.
- 20 fully folded dividers for compartment shelving.
- Top opening compartments are slotted on 2" centers for dividers.
- 16 additional fully folded dividers for top opening models.
- Material hook bar assembly with 3 hooks.

Tailgate

- 11-1/2" high.
- Nylon coated stainless steel cables support and secure the tailgate.
- Tailgate drops down for dock style loading.

Prime Paint

- All body components receive a 5-stage zinc phosphate pretreatment and baked on primer.
- A second primer coating is applied after final body assembly for maximum corrosion resistance.

Undercoating

- Entire body underside is fully undercoated with an automotive grade undercoating.

Mounting Kit

- Mounting Kit furnished as standard.

Warranty

- Original owner lifetime warranty.
- Applies to anything we have manufactured.
- Refer to written RKI warranty.

Revised 04/21/2004

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.